




SERIES FMV

Single Phase, 50/60 Hz
Voltage In: 100-240 V
Voltage Out: 120 or 240 V
Rating: 550 VA-2.16 kVA
 4.6-18 A @ 120 V,
 2.3-6 A @ 240 V

MODEL	FMV3205	FMV3210	FMV3215	FMV3220
Output Rating (VA)	550	1000	1440	2160
Load Current Rating (Amps) 120/240 V	4.6/2.3	8.4/4.2	12/6	18
Input Voltage(s)*	100-240	100-240	100-240	190-240
Output Voltage(s)*	120 or 240	120 or 240	120 or 240	120
Load Regulation (RMS)	± 3.5%	± 3.5%	± 2%	± 2%
1 kHz Forward Transfer Impedance (Ohms) @ 120/240V	< 6/< 30	< 3.6/< 15	< 3.6/< 15	< 2.6/< 10
Leakage Current (µA)	< 100	< 100	< 100	< 100
	UL544, UL1012 for all/UL1262 for FMV3220 only			
CSA	C 22.2, No. 66			
Other Approvals	IEC 601-1, VDE 0750			
Width (Inches) (cm)	5.375 (13.65)	5.375 (13.65)	6.375 (16.2)	11.25 (28.58)
Height (Inches) (cm)	4.5 (11.43)	4.5 (11.43)	5.31 (13.5)	8.5 (21.6)
Depth (Inches) (cm)	7 (17.78)	8 (20.32)	9.5 (24.1)	6.75 (17.15)
Shipping Weight (lbs.) (kg)	20 (9.1)	27 (12.5)	40 (18.1)	55 (25)